MATERIAL SAFETY DATA SHEET This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174 **IDENTITY AND DISTRIBUTOR'S INFORMATION** NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special-0 HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B Manufactured For: Lagasse Brothers, Inc. DOT Hazard Classification: ORM-D Address: 1525 Kuebel Street Identity (trade name as used on label): Address: New Orleans, LA 70123 System Clean Ready to Use Glass & Window Cleaner/ SYC2020 Phone: 800-989-7487 MSDS Number: A06410 Revision-2 EMERGENCY RESPONSE NUMBER: 1-800-255-3924 Date Prepared: 03/16/99 Prepared By: LF/CH NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071 SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION COMPONENTS-CHEMICAL NAMES AND COMMON NAMES **ACGIH** OSHA PEL Carcinogen CAS Number SARA (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) Ref. Source * III LIST TLV (ppm) (ppm) **ETHANOL** 64-17-5 1000 No 1000 d ETHYLENE GLYCOL MONOBUTYL ETHER d 25 111-76-2 25 No ISOBUTANE / PROPANE BLEND 800 75-28-5 No 800 1000 1000 74-98-6 No d SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.984 Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Vapor Density (Air = 1): N/E Evaporation Rate (= 1): N/E Solubility in Water: Slight Water Reactive: No Appearance and Odor: Clear, slightly foamy spray with chemical fragrance SECTION 3 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY as per USA FLAME PROJECTION TEST Flammability Limits in Air by % in Volume: Auto Ignition Temperature NON-FLAMMABLE (aerosols) % LEL: N/E % UEL: N/E N/E FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide. SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. SECTION 4 - REACTIVITY HAZARD DATA STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR Incompatibility (Mat. to avoid): Strong oxidizers and alkalies. Conditions to Avoid: Open flame, welding arcs, heat, sparks. Hazardous Decomposition Products: CO2, CO SECTION 5 - HEALTH HAZARD DATA PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION 1 NOT HAZARDOUS EYE ACUTE EFFECTS: Inhalation: Excessive inhalation of vapors can be harmful and may cause headaches, dizziness, asphyxia, anesthetic effects and possible unconsciousness. Eye Contact: Mild irritant. Skin Contact: Mild irritant. Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage. Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, upper respiratory conditions, liver disease & heart irregularities. **EMERGENCY FIRST AID PROCEDURES** Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. Skin Contact: Wash with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. SECTION 6 - CONTROL AND PROTECTIVE MEASURES Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved bu U.S. Bureau of Mines for organic vapor. Protective Gloves: Latex if skin is easily irritated. Eye Protection: Safety glasses recommended. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Other Protective Clothing & Equipment: None Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions & I or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.